

# AGRIMAX FORCE

|           |                                                   |
|-----------|---------------------------------------------------|
| TIRE SIZE | IF 620/75 R 30 CFO                                |
| UM        | IS STANDARD                                       |
| MACHINERY | ERNTemaschine /<br>HOCHLEISTUNGSTRAKTOR / TRACTOR |
| VERSION   | STANDARD                                          |
| TIRE TYPE | TL                                                |
| LI/SS     | 169 D                                             |

## ABMESSUNGEN IS STANDARD

|          |      |         |                 |
|----------|------|---------|-----------------|
| SW (MM)  | 650  | RIM REC | DW 23 B         |
| OD (MM)  | 1703 | RIM ALT | DW 21 B         |
| SLR (MM) | 759  | ECE     | E11-106R-006496 |
| RC (MM)  | 5100 | SRI     | 800             |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR    | 0.6  | 0.8  | 1.0  | 1.2  | 1.4  | 1.6  | 2.0  | 2.4  |
|---------------|------|------|------|------|------|------|------|------|
| 70            | 2475 | 2845 | 3270 | 3690 | 4110 | 4535 | 4955 | 5275 |
| FROM 65 TO 40 | 2725 | 3130 | 3595 | 4060 | 4520 | 4985 | 5450 | 5800 |
| 30            | 2830 | 3288 | 3735 | 4220 | 4700 | 5180 | 5665 | 6030 |
| 20            | 2940 | 3380 | 3880 | 4380 | 4880 | 5380 | 5885 | 6260 |
| 10            | 3460 | 3975 | 4565 | 5155 | 5740 | 6330 | 6920 | 7365 |
| UPTO 30 CYC   | 3540 | 4065 | 4670 | 5275 | 5875 | 6480 | 7085 | 7540 |
| UPTO 15 CYC   | 4220 | 4850 | 5570 | 6290 | 7005 | 7725 | 8445 | 8990 |
| UPTO 10 CYC   | 4630 | 5320 | 6110 | 6900 | 7680 | 8470 | 9265 | 9860 |
| 10 HT         | 2830 | 3255 | 3735 | 4220 | 4700 | 5180 | 5665 | 6030 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

