

AGRIMAX RT 855

| | |
|---------------------|---|
| TIRE SIZE | 340/85 R 28 |
| UM | IS STANDARD |
| CONSTRUCTION | |
| MACHINERY | SPRAYER / VINEYARD HARVESTER / TRACTOR / HARVESTER / IMPLEMENTS |
| VERSION | STANDARD |
| TL/TT | TL |
| LI/SS | 139 A8/B |



DIMENSIONS IS STANDARD

| | | | |
|-----------------|------|----------------|-----------------|
| SW (MM) | 353 | RIM REC | W 12 |
| OD (MM) | 1315 | RIM ALT | W 11 |
| SLR (MM) | 603 | ECE | E11-106R-008233 |
| RC (MM) | 3963 | SRI | 625 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.6 | 0.8 | 1.0 | 1.2 | 1.4 | 1.6 | 2.0 | 2.4 | 2.8 | 3.2 |
|------------|------|------|------|------|------|------|------|------|------|------|
| 50 | 950 | 1120 | 1290 | 1435 | 1605 | 1750 | 1920 | 2070 | 2260 | 2430 |
| 40 | 950 | 1120 | 1280 | 1435 | 1605 | 1750 | 1920 | 2070 | 2260 | 2430 |
| 30 | 1020 | 1200 | 1385 | 1540 | 1720 | 1880 | 2060 | 2215 | 2425 | 2605 |
| 10 LT | 1275 | 1500 | 1730 | 1925 | 2155 | 2350 | 2580 | 2775 | 3035 | 3260 |
| 10 HT | 1020 | 1200 | 1385 | 1540 | 1720 | 1880 | 2060 | 2215 | 2425 | 3490 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.