

# FLOTATION TR 678

<b>TIRE SIZE</b>	<b>600/40 - 22.5</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	⊠ BIAS
<b>MACHINERY</b>	СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ПРИЦЕП / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ
<b>VERSION</b>	DUAL BEAD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	157 A8
<b>LI/SS FREE ROLLING</b>	169 A8



## РАЗМЕРЫ US STANDARD

<b>USA CODE</b>	94051915	<b>RC (IN)</b>	128.5
<b>SW (IN)</b>	24.2	<b>RIM REC</b>	AG 20.00
<b>OD (IN)</b>	42.7	<b>ECE</b>	E11-106R-006501
<b>SLR (IN)</b>	19.0	<b>PR</b>	20

## LOAD CAPACITY (LBS/TIRE)

<b>MPH / PSI</b>	<b>60</b>
25	12790

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.