

# AW 702

|                           |  |
|---------------------------|--|
| <b>TIRE SIZE</b>          | 7.00 - 12  |
| <b>UM</b>                 | IS STANDARD  |
| <b>CONSTRUCTION</b>       | ⊠ BIAS   |
| <b>MACHINERY</b>          | ПРЕСС-ПОДБОРЩИК /<br>СЕЛЬСКОХОЗЯЙСТВЕННОЕ<br>ОБОРУДОВАНИЕ / ПРИЦЕП /<br>КОМБАЙН /<br>СЕЛЬСКОХОЗЯЙСТВЕННОЕ<br>ОБОРУДОВАНИЕ / ПРИЦЕП |
| <b>VERSION</b>            | ARAMID BELTED  |
| <b>TIRE TYPE</b>          | TL   |
| <b>LI/SS FREE ROLLING</b> | 95 A8  |



## РАЗМЕРЫ IS STANDARD

|                 |      |                |                 |
|-----------------|------|----------------|-----------------|
| <b>SW (MM)</b>  | 185  | <b>RIM REC</b> | 4.25            |
| <b>OD (MM)</b>  | 665  | <b>ECE</b>     | E11-106R-004243 |
| <b>SLR (MM)</b> | 295  | <b>PR</b>      | 6               |
| <b>RC (MM)</b>  | 1948 |                |                 |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 2.50 |
|------------|------|
| 10 FR      | 965  |
| 25 FR      | 820  |
| 30 FR      | 775  |
| 40 FR      | 690  |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.