


RIDEMAX IT 697 (M+S)



| | |
|---------------------|--|
| TYRE SIZE | 710/70 R 38 IND |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | TRACTOR |
| VERSION | STANDARD |
| TL/TT | TL |
| LI/SS | 177 D ; 182 A8 |

DIMENSIONS US STANDARD

| | | | |
|-----------------|----------|----------------|-----------------|
| USA CODE | 94067084 | RC (IN) | 234.3 |
| SW (IN) | 28.2 | RIM REC | DW 23 B |
| OD (IN) | 77.1 | RIM ALT | DW 25 B |
| SLR (IN) | 35.4 | ECE | E11-106R-006762 |

LOAD CAPACITY (LBS/TYRE)

| MPH / PSI | 17 | 23 | 29 | 35 | 41 | 46 |
|-----------|------|-------|-------|-------|-------|-------|
| 40 | 8050 | 9820 | 10790 | 12720 | 14330 | 16090 |
| 30 | 8700 | 10600 | 11650 | 13730 | 15480 | 17380 |
| 25 | 9370 | 11430 | 12550 | 14800 | 16680 | 18740 |
| 20 | 9070 | 11780 | 12940 | 15270 | 17200 | 19310 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.