

FLOTATION 648

TIRE SIZE	850/50 - 30.5
UM	IS STANDARD
CONSTRUCTION	⊠ BIAS
MACHINERY	ENFARDADEIRA DE FENO / CEIFEIRA / ESPALHADOR / CEIFEIRA / IMPLEMENTOS AGRÍCOLAS
VERSÃO	STANDARD
TIRE TYPE	TL
LI/SS DRIVE WHEEL	168 A8/164 B
LI/SS FREE ROLLING	180 A8/176 B



DIMENSÕES IS STANDARD

SW (MM)	850	RIM REC	AG 28.00
OD (MM)	1650	ECE	E11-106R-004564
SLR (MM)	710	PR	12
RC (MM)	4935		

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.10	1.30	1.50
10 FR	9345	10305	11200
20 FR	8410	9275	10080
30 FR	7475	8245	8960
40 FR	6675	7360	8000
50 FR	6010	6625	7100
10 DW	6540	7210	7840
20 DW	5885	6490	7055
30 DW	5230	5770	6270
40 DW	4670	5150	5600
50 DW	4205	4635	5000

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.