


# RIDEMAX FL 690

<b>TIRE SIZE</b>	<b>28L R 26</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	TANKBIL / SLÄPVAGN / ARBETSFORDON / SLÄPVAGN
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	176 A8 ; 173 B



## DIMENSIONER IS STANDARD

<b>SW (MM)</b>	719	<b>RIM REC</b>	DW 25 B
<b>OD (MM)</b>	1590	<b>RIM ALT</b>	DW 23 B
<b>SLR (MM)</b>	695	<b>ECE</b>	E11-106R-002985
<b>RC (MM)</b>	4745	<b>SRI</b>	750

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.8	1.0	1.4	1.6	2.0	2.4	2.8
50	3120	3560	4325	4680	5330	5915	6500
40	3410	3885	4725	5115	5825	6465	7100
30	3820	4355	5295	5730	6525	7240	7955
25	4060	4625	5620	6085	6930	7690	8450
10	4775	5440	6615	7160	8155	9050	9940

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.