


AW 705

| | |
|---------------------------|---|
| TIRE SIZE | 16.0/70 - 20 |
| UM | US STANDARD |
| CONSTRUCTION |  BIAS |
| MACHINERY | ПРЕСС-ПОДБОРЩИК / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ПРИЦЕП / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ |
| VERSION | STANDARD |
| TIRE TYPE | TT |
| LI/SS FREE ROLLING | 151 A8 |



РАЗМЕРЫ US STANDARD

| | | | |
|-----------------|----------|----------------|--------------------|
| USA CODE | 94010189 | RC (IN) | 124.2 |
| SW (IN) | 16.1 | RIM REC | 13.0 |
| OD (IN) | 42.3 | RIM ALT | 12 SDC; 13 SDC; 14 |
| SLR (IN) | 18.9 | ECE | E4-106R-002711 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 44 |
|-----------|-------|
| 5 FR | 10650 |
| 15 FR | 9050 |
| 20 FR | 8520 |
| 25 FR | 7610 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.