


# FLOTATION 558

<b>TIRE SIZE</b>	<b>400/55 - 22.5</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 BIAS
<b>MACHINERY</b>	PRESSE À PAILLE / MOISSONNEUSE / VÉHICULE CITERNE / REMORQUE / MOISSONNEUSE / OUTILLAGE AGRICOLE
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	144 A8/140 B
<b>LI/SS FREE ROLLING</b>	156 A8/152 B



## DIMENSIONS IS STANDARD

<b>SW (MM)</b>	405	<b>RIM REC</b>	AG 11.75
<b>OD (MM)</b>	1020	<b>RIM ALT</b>	12.25; 13.00; AG 13.00
<b>SLR (MM)</b>	445	<b>ECE</b>	E11-106R-005351
<b>RC (MM)</b>	3084	<b>PR</b>	20

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	4.60	4.80	5.00
10 FR	5335	5465	5600
20 FR	4800	4920	5040
30 FR	4265	4375	4480
40 FR	3810	3905	4000
50 FR	3430	3515	3550
10 DW	3730	3830	3920
20 DW	3360	3445	3530
30 DW	2985	3065	3135
40 DW	2665	2735	2800
50 DW	2400	2460	2500

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.