


# AGRIMAX RT 855

<b>TIRE SIZE</b>	<b>520/85 R 50</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	PULVERIZATOR / MAȘINĂ DE RECOLTAT PODGORII / TRACTOR / MAȘINĂ DE RECOLTARE / MAȘINI DE IMPLEMENTARE
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	165 A8/B



## DIMENSIUNI IS STANDARD

<b>SW (MM)</b>	516	<b>RIM REC</b>	DW 16L
<b>OD (MM)</b>	2154	<b>RIM ALT</b>	DW 18 L
<b>SLR (MM)</b>	992	<b>ECE</b>	E11-106R-004895
<b>RC (MM)</b>	6472	<b>SRI</b>	1025

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
<b>50</b>	2425	2785	3195	3605	4020	4430	4845	5150
<b>40</b>	2425	2785	3195	3605	4020	4430	4845	5150
<b>30</b>	2595	2980	3420	3865	4305	4745	5185	5515
<b>10 LT</b>	3250	3730	4285	4835	5390	5940	6495	6905
<b>10 HT</b>	2595	2980	3420	3865	4305	4745	5185	5515

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.