


# AGRIMAX PROCROP

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>VF 270/95 R 38</b>  |
| <b>UM</b>           | IS STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | PULVERIZADOR AGRÍCOLA  |
| <b>VERSÃO</b>       | STEEL BELTED   |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 151 D  |



## DIMENSÕES IS STANDARD

|                 |      |                |                  |
|-----------------|------|----------------|------------------|
| <b>SW (MM)</b>  | 280  | <b>RIM REC</b> | W9               |
| <b>OD (MM)</b>  | 1491 | <b>ECE</b>     | E11-106R-0010173 |
| <b>SLR (MM)</b> | 695  | <b>SRI</b>     | 725              |
| <b>RC (MM)</b>  | 4541 |                |                  |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR           | 1.0  | 1.2  | 1.4  | 1.6  | 2.0  | 2.4  | 2.8  | 3.2  | 3.6  | 4.0  |
|----------------------|------|------|------|------|------|------|------|------|------|------|
| 70                   | 1480 | 1665 | 1855 | 2010 | 2230 | 2355 | 2575 | 2795 | 2985 | 3140 |
| <b>FROM 65 TO 40</b> | 1625 | 1830 | 2040 | 2210 | 2450 | 2590 | 2830 | 3075 | 3280 | 3450 |
| 30                   | 1655 | 1870 | 2080 | 2255 | 2500 | 2640 | 2890 | 3135 | 3345 | 3520 |
| 20                   | 1690 | 1905 | 2120 | 2300 | 2550 | 2695 | 2945 | 3200 | 3415 | 3590 |
| 10                   | 1785 | 2015 | 2240 | 2430 | 2695 | 2850 | 3115 | 3380 | 3610 | 3795 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.