

AGRIMAX RT 855

TIRE SIZE	520/85 R 42
UM	US STANDARD
MACHINERY	SPRAYER / VINEYARD HARVESTER / TRACTOR / HARVESTER / IMPLEMENTS
VERSION	STANDARD
TL/TT	TL
LI/SS	167 A8/B



DIMENSIONS US STANDARD

USA CODE	94040513	RC (IN)	233
SW (IN)	21.26	RIM REC	DW 16 L ; W 16 A ; DD 16
OD (IN)	76.8	RIM ALT	DW 18 A ; DD 18 ; W 18 A ; DD 18 L
SLR (IN)	35.23	ECE	E4-106R-001491

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	35	41	46
30	5000	5820	6650	7460	8280	9090	10220	11180	12010
25	5000	5820	6650	7460	8280	9090	10220	11180	12010
20	5360	6240	7110	7990	8860	9730	10930	11960	12850
5 LT	6710	7800	8910	10000	11100	12190	13690	14980	16100
5 HT	5360	6240	7110	7990	8860	9730	10930	11960	12850

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.