

AGRIMAX SPARGO

VF 320/90 R 50

UM IS STANDARD

CONSTRUCTION  RADIAL

MACHINERY TRAKTÖR

VERSION STANDARD

TIRE TYPE TL

169 D



UNDEFINED IS STANDARD

| | | | |
|----------|------|---------|----------------------------|
| SW (MM) | 323 | RIM REC | W 11 |
| OD (MM) | 1846 | RIM ALT | W 10; DW 10; W 10 L; DW 11 |
| SLR (MM) | 865 | ECE | E11-106R-007204 |
| RC (MM) | 5650 | SRI | 875 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 1.2 | 1.4 | 1.6 | 1.8 | 2.0 | 2.2 | 2.4 | 2.6 | 2.8 | 3.0 | 3.2 | 3.4 | 3.6 | 3.8 | 4.0 | 4.2 | 4.4 | 4.8 |
|---------------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|
| 70 | 2415 | 2685 | 2955 | 3085 | 3220 | 3330 | 3435 | 3595 | 3760 | 3810 | 3865 | 4105 | 4350 | 4455 | 4565 | 4775 | 4990 | 5365 |
| FROM 65 TO 40 | 2610 | 2900 | 3190 | 3335 | 3480 | 3600 | 3715 | 3890 | 4060 | 4120 | 4180 | 4440 | 4700 | 4815 | 4930 | 5165 | 5395 | 5800 |
| 30 | 2665 | 2960 | 3260 | 3405 | 3555 | 3675 | 3790 | 3970 | 4145 | 4205 | 4265 | 4530 | 4800 | 4915 | 5035 | 5270 | 5510 | 5920 |
| 20 | 2720 | 3020 | 3320 | 3475 | 3625 | 3745 | 3865 | 4045 | 4225 | 4285 | 4350 | 4620 | 4890 | 5010 | 5130 | 5375 | 5615 | 6035 |
| 10 | 2875 | 3190 | 3510 | 3670 | 3830 | 3960 | 4085 | 4275 | 4470 | 4530 | 4595 | 4885 | 5170 | 5300 | 5425 | 5680 | 5935 | 6380 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.