

# AGRIMAX FORTIS

|                     |                    |
|---------------------|--------------------|
| <b>TIRE SIZE</b>    | <b>710/75 R 42</b> |
| <b>UM</b>           | US STANDARD        |
| <b>CONSTRUCTION</b> |                    |
| <b>MACHINERY</b>    | TRACTOR            |
| <b>VERSION</b>      | STANDARD           |
| <b>TL/TT</b>        | TL                 |
| <b>LI/SS</b>        | 175 D ; 172 E      |



## DIMENSIONS US STANDARD

|                 |          |                |                |
|-----------------|----------|----------------|----------------|
| <b>USA CODE</b> | 94034710 | <b>RC (IN)</b> | 252.2          |
| <b>SW (IN)</b>  | 28.2     | <b>RIM REC</b> | DW 23 B        |
| <b>OD (IN)</b>  | 84.0     | <b>RIM ALT</b> | DW 25 B        |
| <b>SLR (IN)</b> | 38.2     | <b>ECE</b>     | E4-106R-001835 |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 9    | 12    | 15    | 17    | 20    | 23    | 29    | 35    |
|-----------|------|-------|-------|-------|-------|-------|-------|-------|
| 45        | 6670 | 7780  | 8750  | 9720  | 10700 | 11530 | 12790 | 13890 |
| 40        | 7310 | 8520  | 9590  | 10650 | 11720 | 12630 | 14000 | 15210 |
| 30        | 7670 | 8950  | 10060 | 11190 | 12300 | 13260 | 14700 | 15970 |
| 25        | 8000 | 9340  | 10500 | 11670 | 12840 | 13830 | 15340 | 16670 |
| 20        | 8400 | 9800  | 11020 | 12250 | 13470 | 14530 | 16100 | 17490 |
| 5 LT      | 9790 | 11420 | 12850 | 14270 | 15710 | 16930 | 18760 | 20390 |
| 5 HT      | 8400 | 9800  | 11020 | 12250 | 13470 | 14530 | 16100 | 17490 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.