

# AW 705

<b>TIRE SIZE</b>	<b>14.0/65 - 16</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	❖ BIAS
<b>MACHINERY</b>	ПРЕСС-ПОДБОРЩИК / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ПРИЦЕП / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TT
<b>LI/SS FREE ROLLING</b>	142 A8



## РАЗМЕРЫ US STANDARD

<b>USA CODE</b>	94009923	<b>RC (IN)</b>	100.4
<b>SW (IN)</b>	13.9	<b>RIM REC</b>	11.0
<b>OD (IN)</b>	34.3	<b>ECE</b>	E4-106R-001901
<b>SLR (IN)</b>	15.3	<b>PR</b>	14

## LOAD CAPACITY (LBS/TIRE)

<b>MPH / PSI</b>	<b>58</b>
5 FR	8180
15 FR	6960
20 FR	6550
25 FR	5840

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.