


# AS 507

<b>TIRE SIZE</b>	<b>185/65 - 15</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 BIAS
<b>MACHINERY</b>	ATTREZZI AGRICOLI / RIMORCHIO / ATTREZZI AGRICOLI
<b>VERSIONE</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	76 A8
<b>LI/SS FREE ROLLING</b>	89 A8



## DIMENSIONI US STANDARD

<b>CODICE USA</b>	94019489	<b>RC (IN)</b>	74.6
<b>SW (IN)</b>	7.3	<b>RIM REC</b>	5½ J
<b>OD (IN)</b>	25.2	<b>ECE</b>	E4-106R-002185
<b>SLR (IN)</b>	11.9	<b>PR</b>	4

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	41
5 FR	1790
15 FR	1520
20 FR	1430
25 FR	1280
5 DW	1230
15 DW	1050
20 DW	990
25 DW	880

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.