


AGRIMAX RT 955

TIRE SIZE	300/95 R 52
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	FELDSPRITZE / TRAUBENERNTEMASCHINE / ERNTEMASCHINE / LANDWIRTSCHAFTLICHE GERÄTE
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	151 A8/B



ABMESSUNGEN US STANDARD

USA-CODE	94029747	RC (IN)	227.3
SW (IN)	11.6	RIM REC	W 9
OD (IN)	74.4	RIM ALT	W 10 ; W 11 ; DW 10 ; DW 11
SLR (IN)	35.0	ECE	E4-106R-001484

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	12	17	23	29	35	41	46	52	58	64
30	2980	3880	4720	5180	5480	6020	6550	7080	7600	-
25	2980	3880	4720	5180	5480	6020	6550	7080	7600	-
20	3190	4160	5060	5540	5870	6440	7010	7580	8150	-
5	3540	4450	5480	6500	7540	7760	8670	9590	10500	11410

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.