

# AGRIMAX RT 855

<b>TIRE SIZE</b>	<b>480/80 R 42</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	
<b>MACHINERY</b>	SPRAYER / VINEYARD HARVESTER / TRACTOR / HARVESTER / IMPLEMENTS
<b>VERSION</b>	STANDARD
<b>TL/TT</b>	TL
<b>LI/SS</b>	151 A8/B



## DIMENSIONS US STANDARD

<b>USA CODE</b>	94021796	<b>RC (IN)</b>	216.3
<b>SW (IN)</b>	18.9	<b>RIM REC</b>	W 16 A ; DD 16 ; DW 16 A
<b>OD (IN)</b>	72.2	<b>RIM ALT</b>	DD 16 L ; DW 16 L ; W 16 L
<b>SLR (IN)</b>	32.9	<b>ECE</b>	E4-106R-000791

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23
30	4190	4870	5560	6240	6920	7600
25	4190	4870	5560	6240	6920	7600
20	4490	5210	5950	6680	7420	8150
5 LT	5610	6530	7450	8370	9280	10200
5 HT	4490	5210	5950	6680	7420	8150

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.