


# AGRIMAX RT 855

<b>TIRE SIZE</b>	<b>320/85 R 34</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	FELDSPRITZE / TRAUBENERNTEMASCHINE / TRACTOR / ERNTEMASCHINE / LANDWIRTSCHAFTLICHE GERÄTE
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	141 A8/B



## ABMESSUNGEN US STANDARD

<b>USA-CODE</b>	94040414	<b>RC (IN)</b>	168.5
<b>SW (IN)</b>	13.0	<b>RIM REC</b>	W 11
<b>OD (IN)</b>	55.4	<b>RIM ALT</b>	W 9 ; W 10
<b>SLR (IN)</b>	25.4	<b>ECE</b>	E4-106R-001395

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	17	23	29	35	41	46	52
<b>30</b>	2050	2390	3130	3810	4140	4430	4830	5220	5680
<b>25</b>	2050	2390	3130	3810	4140	4430	4830	5220	5680
<b>20</b>	2190	2560	3350	4080	4440	4750	5180	5600	6080
<b>5 LT</b>	2740	3210	4200	5100	5570	5940	6480	7010	7620
<b>5 HT</b>	2190	2560	3350	4080	4440	4750	5180	5600	6080

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.