


# AGRIMAXFACTOR

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>620/70 R 42</b>   |
| <b>UM</b>           | IS STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | ТРАКТОР-ТЯГАЧ  |
| <b>VERSION</b>      | STANDARD   |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 166 D ; 169 A8   |



## РАЗМЕРЫ IS STANDARD

|                 |      |                |                 |
|-----------------|------|----------------|-----------------|
| <b>SW (MM)</b>  | 625  | <b>RIM REC</b> | DW 20 B         |
| <b>OD (MM)</b>  | 1935 | <b>RIM ALT</b> | DW18L; W18L     |
| <b>SLR (MM)</b> | 876  | <b>ECE</b>     | E11-106R-007765 |
| <b>RC (MM)</b>  | 5801 | <b>SRI</b>     | 925             |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.6  | 0.8  | 1.0  | 1.2  | 1.4  | 1.6  | 2.0  | 2.4  |
|------------|------|------|------|------|------|------|------|------|
| 65         | 2495 | 2865 | 3290 | 3710 | 4135 | 4560 | 4985 | 5300 |
| 50         | 2620 | 3010 | 3455 | 3900 | 4345 | 4790 | 5235 | 5565 |
| 40         | 2730 | 3135 | 3600 | 4065 | 4530 | 4995 | 5460 | 5800 |
| 30         | 2865 | 3295 | 3780 | 4270 | 4755 | 5245 | 5730 | 6095 |
| 10 LT      | 3340 | 3840 | 4410 | 4975 | 5545 | 6115 | 6680 | 7105 |
| 10 HT      | 2865 | 3295 | 3780 | 4270 | 4755 | 5245 | 5730 | 6095 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.