


# AS 504

<b>TIRE SIZE</b>	<b>7.50 - 18</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 BIAS
<b>MACHINERY</b>	TELEHANDLER / FIELD TRAILER / IMPLEMENTS / TELEHANDLER
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TT
<b>LI/SS DRIVE WHEEL</b>	94 A8
<b>LI/SS FREE ROLLING</b>	106 A8



## DIMENSIONS US STANDARD

<b>USA CODE</b>	94026579	<b>RC (IN)</b>	104.3
<b>SW (IN)</b>	8.2	<b>RIM REC</b>	5.50 F
<b>OD (IN)</b>	33.6	<b>RIM ALT</b>	4.50 E; 6.00 F; 5.00 F
<b>SLR (IN)</b>	16.0	<b>PR</b>	6

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	33
5 FR	2930
15 FR	2490
20 FR	2350
25 FR	2090
5 DW	2070
15 DW	1750
20 DW	1650
25 DW	1480

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.