

AS 504

TIRE SIZE	10.0/80 - 12
UM	IS STANDARD
CONSTRUCTION	⊠ BIAS
MACHINERY	ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК / ПРИЦЕП ДЛЯ ПОЛЕВЫХ РАБОТ / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК
VERSION	STANDARD
TIRE TYPE	TL
LI/SS DRIVE WHEEL	109 A8
LI/SS FREE ROLLING	121 A8



РАЗМЕРЫ IS STANDARD

SW (MM)	270	RIM REC	9.00
OD (MM)	730	RIM ALT	7.0
SLR (MM)	335	ECE	E11-106R-006010
RC (MM)	2233		

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	3.90
10 FR	2030
25 FR	1725
30 FR	1625
40 FR	1450
10 DW	1440
25 DW	1225
30 DW	1155
40 DW	1030

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.