


AGRIMAX SPARGO

TIRE SIZE	VF 320/90 R 42
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	TRACTOR
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	163 D



DIMENSIONI IS STANDARD

SW (MM)	323	RIM REC	W 11
OD (MM)	1642	RIM ALT	W 10; DW 10; W 10 L; DW 11
SLR (MM)	764	ECE	E11-106R-007813
RC (MM)	4995	SRI	775

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.2	1.4	1.6	1.8	2.0	2.2	2.4	2.6	2.8	3.0	3.2	3.4	3.6	3.8	4.0	4.2	4.4
70	2165	2440	2665	2800	2935	3025	3115	3270	3430	3565	3700	3815	3925	4040	4150	4330	4510
FROM 65 TO 40	2340	2635	2880	3025	3170	3270	3365	3535	3705	3855	4000	4120	4245	4365	4485	4680	4875
30	2390	2690	2940	3085	3235	3335	3435	3610	3785	3935	4080	4205	4330	4455	4580	4780	4975
20	2435	2740	2995	3145	3300	3400	3500	3680	3855	4010	4160	4285	4415	4540	4665	4870	5070
10	2580	2900	3170	3330	3490	3595	3705	3890	4080	4240	4400	4535	4670	4805	4940	5155	5365

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.