

# TR 315

|                     |   |
|---------------------|---|
| <b>TIRE SIZE</b>    | <b>31X15.50 - 15</b>  |
| <b>UM</b>           | IS STANDARD   |
| <b>CONSTRUCTION</b> |  BIAS  |
| <b>MACHINERY</b>    | СЕЛЬСКОХОЗЯЙСТВЕННОЕ<br>ОБОРУДОВАНИЕ / МАШИНА ДЛЯ<br>СБОРА ФРУКТОВ / ТРАНШЕЙНЫЙ<br>ЭКСКАВАТОР / КОМБАЙН /<br>СЕЛЬСКОХОЗЯЙСТВЕННОЕ<br>ОБОРУДОВАНИЕ |
| <b>VERSION</b>      | STANDARD  |
| <b>TIRE TYPE</b>    | TL  |



## РАЗМЕРЫ IS STANDARD

|                 |      |                |                |
|-----------------|------|----------------|----------------|
| <b>SW (MM)</b>  | 390  | <b>RIM REC</b> | 13 LB          |
| <b>OD (MM)</b>  | 800  | <b>ECE</b>     | E4-106R-002333 |
| <b>SLR (MM)</b> | 354  | <b>PR</b>      | 12             |
| <b>RC (MM)</b>  | 2320 |                |                |

## LOAD CAPACITY (KG/TIRE)

|                   |             |
|-------------------|-------------|
| <b>KM/H / BAR</b> | <b>5.10</b> |
| 50                | 1650        |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.