


# AW 729

<b>TIRE SIZE</b>	<b>380/55 - 17</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 BIAS
<b>MACHINERY</b>	PRESĂ DE BALOTAT / MAȘINI DE IMPLEMENTARE / REMORCĂ / MAȘINĂ DE RECOLTARE / MAȘINI DE IMPLEMENTARE
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	122 A8
<b>LI/SS FREE ROLLING</b>	134 A8



## DIMENSIUNI US STANDARD

<b>USA CODE</b>	94074150	<b>RC (IN)</b>	100.8
<b>SW (IN)</b>	15.2	<b>RIM REC</b>	13.00
<b>OD (IN)</b>	33.5	<b>RIM ALT</b>	13; W 13
<b>SLR (IN)</b>	14.8	<b>ECE</b>	E11-106R-008727

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	38
5 FR	6550
15 FR	5570
20 FR	5240
25 FR	4680
5 DW	4630
15 DW	3940
20 DW	3700
25 DW	3300

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.