

# AGRIMAX RT 855

<b>TIRE SIZE</b>	<b>520/85 R 38</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	ОПРЫСКИВАТЕЛЬ / КОМБАЙН ДЛЯ УБОРКИ ВИНОГРАДА / ТРАКТОР-ТЯГАЧ / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	170 A8/B



## РАЗМЕРЫ US STANDARD

<b>USA CODE</b>	94038374	<b>RC (IN)</b>	220.3
<b>SW (IN)</b>	20.3	<b>RIM REC</b>	DW 16 L
<b>OD (IN)</b>	72.8	<b>RIM ALT</b>	DW 18 L ; DD 16 L
<b>SLR (IN)</b>	33.3	<b>ECE</b>	E4-106R-001411

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	17	23	29	35	41	46	52
<b>30</b>	4780	5640	7180	8540	9790	10450	11510	12430	13230
<b>25</b>	4780	5640	7180	8540	9790	10450	11510	12430	13230
<b>20</b>	5130	6040	7690	9150	10480	11190	12320	13300	14150
<b>5 LT</b>	6420	7560	9620	11450	13120	14010	15420	16670	17720
<b>5 HT</b>	5130	6040	7690	9150	10480	11190	12320	13300	14150

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.