

# EARTHMAX SR 468

|                  |                        |
|------------------|------------------------|
| <b>TIRE SIZE</b> | <b>27.00 R 49</b>      |
| <b>UM</b>        | IS STANDARD            |
| <b>MACHINERY</b> | RIGID DUMP TRUCK       |
| <b>VERSION</b>   | CUT RESISTANT COMPOUND |
| <b>TL/TT</b>     | TL                     |
| <b>LI/SS</b>     | 226 B                  |



## DIMENSIONS IS STANDARD

|                 |           |                    |     |
|-----------------|-----------|--------------------|-----|
| <b>OD (MM)</b>  | 2720      | <b>RIM ALT</b>     | -   |
| <b>SLR (MM)</b> | 1235      | <b>TRA CODE</b>    | E4  |
| <b>RC (MM)</b>  | 8351      | <b>STAR RATING</b> | ★★★ |
| <b>RIM REC</b>  | 19.50/4.0 |                    |     |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 6.00  | 6.25  | 6.50  | 6.75  | 7.00  | 7.25  | 7.50  | 7.75  | 8.00  |
|------------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| 50         | 23600 | 25000 | 25750 | 26500 | 27250 | 27250 | 28000 | 29000 | 30000 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.