

AGRIMAX RT 657

| | |
|---------------------|--|
| TIRE SIZE | 320/65 R 18 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | MAȘINĂ DE RECOLTAT PODGORII / TRACTOR / MAȘINĂ DE RECOLTARE |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 125 A8/B |



DIMENSIUNI IS STANDARD

| | | | |
|-----------------|------|----------------|-----------------|
| SW (MM) | 310 | RIM REC | W 10 |
| OD (MM) | 885 | RIM ALT | W 9; W 11 |
| SLR (MM) | 400 | ECE | E11-106R-008145 |
| RC (MM) | 2667 | SRI | 425 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.6 | 0.8 | 1.0 | 1.2 | 1.4 | 1.6 | 1.8 | 2.0 | 2.8 | 3.2 |
|------------|-----|-----|------|------|------|------|------|------|------|------|
| 50 | 545 | 645 | 745 | 825 | 925 | 1010 | 1205 | 1340 | 1505 | 1650 |
| 40 | 545 | 645 | 745 | 825 | 925 | 1010 | 1205 | 1340 | 1505 | 1650 |
| 30 | 585 | 695 | 800 | 885 | 995 | 1080 | 1295 | 1435 | 1615 | 1770 |
| 10 LT | 735 | 865 | 1000 | 1110 | 1245 | 1355 | 1620 | 1795 | 2020 | 2215 |
| 10 HT | 585 | 695 | 800 | 885 | 995 | 1080 | 1295 | 1435 | 1615 | 1770 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.