

EARTHMAX SR 49 M



EARTHMAX
RADIAL OTR TIRES

EARTHMAX SR 49 M

EARTHMAX SR 49 M is an All Steel radial tyre with a special non-directional pattern designed for load haul dumps (LHD), low profile dump trucks (LPDT), loaders and dozers operating in severe rocky conditions primarily in underground mining. EARTHMAX SR 49 M is ideal for severe operations requiring exceptional traction and stability.



	SIZE	TT/TL	TRA CODE	STAR RATING	LI/SS	RIM		TKPH (TK/H)	OW (MM) (mm)	OD (mm)	SLR (mm)	RC (mm)	TREAD DEPTH (MM)	VERSION
						REC RIM	ALT RIM							
														
Ø25"	26.5 R 25	TL	SH4	****	-	22.00/3.0	-	0	708	1782	801	5297	56	CR
	26.5 R 25	TL	E4/L4	**/*	193 B 202 A2	22.00/3.0	-	165	708	1782	801	5297	56	CR
	26.5 R 25	TL	E4/L4	****/***	-	22.00/3.0	-	0	708	1782	801	5297	56	CR
	26.5 R 25	TL	L4	*	202 A2	22.00/3.0	-	0	708	1782	801	5297	56	CR

CR: CUT RESISTANT COMPOUND

TECHNOLOGIES		PERFORMANCES	
	 E4/L4/SH4		
	 B 223 kg		

Permissible tolerances: O.D. 2%-S.W. 2%-RC 2.5%-LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balakrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

GB – 23/09/2026

	SIZE	TT/TL	TRA CODE	STAR RATING	LI/SS	RIM		TKPH (TK/H)	OW (MM) (mm)	OD (mm)	SLR (mm)	RC (mm)	TREAD DEPTH (MM)	VERSION
						REC RIM	ALT RIM							
														
	26.5 R 25	TL	L4	**	209 A2	22.00/3.0	-	0	708	1782	801	5297	56	CR
Ø29"	29.5 R 29	TL	SH4	****	-	25.00/3.5	24.00/3.5 26.00/3.5	0	786	2006	906	6320	60	CR
	29.5 R 29	TL	L4	***	223 A2	25.00/3.5	24.00/3.5 26.00/3.5	0	786	2006	906	6320	60	CR

CR: CUT RESISTANT COMPOUND



TECHNOLOGIES				PERFORMANCES			
		E4/L4/SH4					
		B 223 kg					

Permissible tolerances: O.D. 2%-S.W. 2%-RC 2.5%-LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balakrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

GB – 23/09/2026