


RIDEMAX FL 693 M



TIRE SIZE	VF 500/50 R 17
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	TANKER / TRAILER / IMPLEMENTS
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	156 D

DIMENSIONS IS STANDARD

SW (MM)	503	RIM REC	16.00
OD (MM)	932	ECE	E11-106R-007200
SLR (MM)	422	SRI	450
RC (MM)	2880		

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.8	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0	4.5	5.0
70	1095	1385	1675	1860	2150	2440	2695	2950	3240	3460	3640
65	1200	1520	1840	2040	2360	2680	2960	3240	3560	3800	4000
50	1455	1840	2230	2470	2860	3245	3585	3925	4310	4600	4840
40	1635	2070	2505	2775	3210	3645	4030	4410	4845	5170	5440
25	1900	2405	2910	3225	3730	4235	4680	5120	5625	6005	6320
10	2160	2740	3315	3675	4250	4825	5330	5835	6410	6840	7200

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.