

AGRIMAX RT 855

TIRE SIZE	380/85 R 30
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	ОПРЫСКИВАТЕЛЬ / КОМБАЙН ДЛЯ УБОРКИ ВИНОГРАДА / ТРАКТОР-ТЯГАЧ / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ
VERSION	SPECIAL
TIRE TYPE	TL
LI/SS	135 A8/B



РАЗМЕРЫ US STANDARD

USA CODE	94033096	RC (IN)	165.0
SW (IN)	15.0	RIM REC	W 12
OD (IN)	55.4	RIM ALT	W 11; W 13
SLR (IN)	24.9	ECE	E4-106R-000594

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23
30	2650	3090	3520	3950	4380	4800
25	2650	3090	3520	3950	4380	4800
20	2830	3300	3760	4220	4680	5150
5 LT	3550	4130	4720	5290	5870	6450
5 HT	2830	3300	3760	4220	4680	5150

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.