

# AGRIMAX RT 657

<b>TIRE SIZE</b>	<b>540/65 R 24</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	SKÖRDEMASKIN FÖR VINGÅRD / TRAKTOR / SKÖRDEMASKIN
<b>VERSION</b>	SPECIAL
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	146 D ; 149 A8



## DIMENSIONER IS STANDARD

<b>SW (MM)</b>	530	<b>RIM REC</b>	W 16 L
<b>OD (MM)</b>	1312	<b>RIM ALT</b>	W 18 L
<b>SLR (MM)</b>	590	<b>ECE</b>	E4-106R-000773
<b>RC (MM)</b>	3930	<b>SRI</b>	625

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
<b>65</b>	1440	1680	1890	2100	2310	2490	2760	3000
<b>50</b>	1515	1765	1985	2205	2430	2615	2900	3150
<b>40</b>	1560	1820	2050	2275	2505	2700	2990	3250
<b>30</b>	1660	1935	2175	2415	2660	2865	3175	3450
<b>10 LT</b>	1930	2255	2535	2815	3100	3340	3700	4020
<b>10 HT</b>	1660	1935	2175	2415	2660	2865	3175	3450

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.