


AGRIMAX V- FLECTO

| | |
|---------------------|--|
| TIRE SIZE | VF 650/75 R 42 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | HOCHLEISTUNGSTRAKTOR / TRACTOR |
| VERSION | SPECIAL |
| TIRE TYPE | TL |
| LI/SS | 180 D |



ABMESSUNGEN US STANDARD

| | | | |
|-----------------|----------|----------------|------------------|
| USA-CODE | 94514427 | RC (IN) | 241.9 |
| SW (IN) | 26.8 | RIM REC | DW 23 B |
| OD (IN) | 80.9 | RIM ALT | DW 21 B |
| SLR (IN) | 35.2 | ECE | E11-106R-0011304 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 9 | 12 | 14 | 17 | 20 | 23 | 29 |
|---------------|-------|-------|-------|-------|-------|-------|-------|
| 45 | 8020 | 9300 | 10580 | 12040 | 13320 | 14590 | 16050 |
| FROM 40 TO 25 | 8820 | 10230 | 11640 | 13230 | 14640 | 16050 | 17640 |
| 20 | 8990 | 10430 | 11870 | 13490 | 14920 | 16370 | 17990 |
| 12 | 9170 | 10640 | 12100 | 13760 | 15220 | 16690 | 18340 |
| 5 | 9700 | 11240 | 12800 | 14550 | 16090 | 17650 | 19400 |
| UPTO 20 CYC | 10010 | 11610 | 13200 | 15010 | 16610 | 18210 | 20020 |
| UPTO 10 CYC | 11950 | 13860 | 15760 | 17920 | 19830 | 21740 | 23900 |
| UPTO 5CYC | 13090 | 15190 | 17280 | 19640 | 21740 | 23830 | 26190 |
| 5 HT | 8990 | 10430 | 11870 | 13490 | 14920 | 16370 | 17990 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.