


# AGRIMAX RT 765

<b>TIRE SIZE</b>	<b>520/70 R 38</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	SPRAYER / TRACTOR / VINEYARD HARVESTER / HARVESTER / IMPLEMENTS
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	150 D



## DIMENSIONS IS STANDARD

<b>SW (MM)</b>	516	<b>RIM REC</b>	W 16 L
<b>OD (MM)</b>	1749	<b>RIM ALT</b>	W 15 L; W 18 L
<b>SLR (MM)</b>	793	<b>ECE</b>	E11-106R-005525
<b>RC (MM)</b>	5300	<b>SRI</b>	825

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6
65	1845	2145	2450	2750	3050	3350
50	1940	2255	2570	2890	3205	3520
40	2020	2350	2680	3010	3340	3670
30	2125	2470	2815	3165	3510	3855
10 LT	2470	2875	3280	3685	4090	4490
10 HT	2125	2470	2815	3165	3510	3855

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.