

FL 630 SUPER

| | |
|---------------------|--|
| TIRE SIZE | 750/60 R 30.5 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | ESPALHADOR / CISTERNA MÓVEL / REBOQUE / IMPLEMENTOS AGRÍCOLAS |
| VERSÃO | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 181 D |



DIMENSÕES IS STANDARD

| | | | |
|-----------------|------|----------------|----------------|
| SW (MM) | 754 | RIM REC | AG 24.00 |
| OD (MM) | 1675 | ECE | E4-106R-001499 |
| SLR (MM) | 746 | SRI | 800 |
| RC (MM) | 5115 | | |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.8 | 1.0 | 1.2 | 1.6 | 2.0 | 2.4 | 2.8 | 3.2 | 3.6 | 4.0 |
|------------|------|------|------|------|------|-------|-------|-------|-------|-------|
| 70 | 2405 | 2780 | 3155 | 3835 | 4435 | 5110 | 5785 | 6235 | 6910 | 7510 |
| 65 | 2640 | 3055 | 3465 | 4210 | 4870 | 5610 | 6355 | 6850 | 7590 | 8250 |
| 50 | 3200 | 3700 | 4195 | 5095 | 5895 | 6790 | 7690 | 8290 | 9190 | 9985 |
| 40 | 3595 | 4155 | 4715 | 5725 | 6620 | 7630 | 8640 | 9315 | 10325 | 11220 |
| 25 | 4175 | 4825 | 5475 | 6650 | 7695 | 8865 | 10040 | 10820 | 11995 | 13035 |
| 10 | 4755 | 5500 | 6240 | 7575 | 8765 | 10100 | 11435 | 12330 | 13665 | 14850 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.