

# EM 936

|                     |                         |
|---------------------|-------------------------|
| <b>TIRE SIZE</b>    | <b>9.00 - 20</b>        |
| <b>UM</b>           | US STANDARD             |
| <b>CONSTRUCTION</b> | ⊠ BIAS                  |
| <b>MACHINERY</b>    | EXCAVATOR / TELEHANDLER |
| <b>VERSION</b>      | SPECIAL                 |
| <b>TIRE TYPE</b>    | TT                      |
| <b>LI/SS</b>        | 140 B                   |



## DIMENSIONS US STANDARD

|                 |          |                 |          |
|-----------------|----------|-----------------|----------|
| <b>USA CODE</b> | 94032884 | <b>RIM REC</b>  | 7.0      |
| <b>OD (IN)</b>  | 39.8     | <b>RIM ALT</b>  | 6.5; 7.5 |
| <b>SLR (IN)</b> | 18.9     | <b>PR</b>       | 14       |
| <b>RC (IN)</b>  | 120.9    | <b>TRA CODE</b> | E2       |

## LOAD CAPACITY (LBS/TIRE)

|                  |            |
|------------------|------------|
| <b>MPH / PSI</b> | <b>102</b> |
| 30               | 5510       |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.