

AGRIMAX RT 765

| | |
|---------------------|--|
| TIRE SIZE | 420/70 R 24 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | BESPRUTNINGSBIL / TRAKTOR / SKÖRDEMASKIN FÖR VINGÅRD / SKÖRDEMASKIN / ARBETSFORDON |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 130 D |



DIMENSIONER US STANDARD

| | | | |
|-----------------|----------|----------------|-----------------|
| USA CODE | 94063024 | RC (IN) | 144.9 |
| SW (IN) | 16.5 | RIM REC | W 13 |
| OD (IN) | 49.1 | RIM ALT | W 12; W 14 L |
| SLR (IN) | 21.8 | ECE | E11-106R-005826 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 9 | 12 | 15 | 17 | 20 | 23 |
|-----------|------|------|------|------|------|------|
| 40 | 2300 | 2690 | 3060 | 3440 | 3810 | 4190 |
| 30 | 2420 | 2820 | 3220 | 3620 | 4010 | 4400 |
| 25 | 2540 | 2940 | 3360 | 3770 | 4190 | 4600 |
| 20 | 2660 | 3090 | 3530 | 3960 | 4390 | 4820 |
| 5 LT | 3100 | 3600 | 4110 | 4620 | 5130 | 5620 |
| 5 HT | 2660 | 3090 | 3530 | 3960 | 4390 | 4820 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.