DATA SHEET

PRINTED ON
21-04-2026

EARTHMAX SR 25 PLUS

TIRE SIZE	**14.00 R 24**
UM	IS STANDARD
CONSTRUCTION	RADIAL
MACHINERY	MOTOLIVELLATRICE / PALA CARICATRICE / DOZER / PALA CARICATRICE / MOTOLIVELLATRICE / DOZER
VERSIONE	CUT RESISTANT COMPOUND
TIRE TYPE	TL
LI/SS	153 A8 ; 175 A2

DIMENSIONI IS STANDARD

OD (MM)	1372	**RIM ALT**	9.00GR
SLR (MM)	626	**TRA CODE**	G2/L2
RC (MM)	4146	**STAR RATING**	★
RIM REC	8.00TG		

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	2.00	2.25	2.50	2.75	3.00	3.25	3.50	3.75	5.25	5.50
40	2240	2430	2650	2800	3000	3250	3350	3650	-	-
10	-	-	-	-	-	-	-	-	6700	6900

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..