


# AGRIMAXFACTOR

<b>TIRE SIZE</b>	<b>710/70 R 42</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	TRATTORE
<b>VERSIONE</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	173 D ; 176 A8



## DIMENSIONI US STANDARD

<b>CODICE USA</b>	94070169	<b>RC (IN)</b>	244.0
<b>SW (IN)</b>	28.2	<b>RIM REC</b>	DW 23 B
<b>OD (IN)</b>	81.1	<b>RIM ALT</b>	DW 25 B
<b>SLR (IN)</b>	36.8	<b>ECE</b>	E11-106R-007526

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35
40	6730	7740	8880	10030	11180	12320	13470	14330
30	7080	8130	9340	10540	11740	12940	14150	15050
25	7360	8450	9710	10960	12210	13470	14720	15650
15	7750	8910	10220	11540	12860	14170	15500	16480
5 LT	9030	10370	11920	13450	14980	16520	18050	19200
5 HT	7750	8910	10220	11540	12860	14170	15500	16480

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.