

# AGRIMAX V- FLECTO

**VF 340/85 R 28**

<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	YÜKSEK GÜÇTE TRAKTÖR / TRAKTÖR
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
	139 D



## UNDEFINED US STANDARD

<b>USA CODE</b>	94076369	<b>RC (IN)</b>	150.9
<b>SW (IN)</b>	14.0	<b>RIM REC</b>	W 12
<b>OD (IN)</b>	50.8	<b>RIM ALT</b>	W 11
<b>SLR (IN)</b>	22.5	<b>ECE</b>	E11-106R-0010342

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23
45	2680	3110	3550	3990	4430	4870
<b>FROM 40 TO 25</b>	2940	3430	3900	4390	4870	5360
20	3000	3480	3980	4460	4960	5460
12	3050	3560	4060	4560	5060	5570
5	3530	4710	5890	7050	8210	9390
<b>*UPTO 5 CYC WITH FRONT LOADER</b>	4120	4790	5470	6140	6810	7500
10HT	3000	3480	3980	4460	4960	5460

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.