


# AGRIMAX SPARGO

|              |  |
|--------------|--|
| TIRE SIZE    | VF 380/85 R 38   |
| UM           | US STANDARD  |
| CONSTRUCTION |  RADIAL |
| MACHINERY    | TRATOR   |
| VERSÃO       | STANDARD   |
| TIRE TYPE    | TL   |
| LI/SS        | 161 D  |



## DIMENSÕES US STANDARD

|            |          |         |                |
|------------|----------|---------|----------------|
| CÓDIGO USA | 94045303 | RC (IN) | 190.2          |
| SW (IN)    | 15.0     | RIM REC | W 13 A         |
| OD (IN)    | 63.1     | RIM ALT | W 12           |
| SLR (IN)   | 28.7     | ECE     | E4-106R-001482 |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI     | 17   | 20   | 23   | 26   | 29   | 32   | 35   | 38   | 41    | 44    | 46    |
|---------------|------|------|------|------|------|------|------|------|-------|-------|-------|
| 45            | 5470 | 6120 | 6670 | 7050 | 7320 | 7600 | 7880 | 8250 | 8620  | 8900  | 9270  |
| FROM 40 TO 25 | 6010 | 6730 | 7350 | 7750 | 8050 | 8360 | 8670 | 9080 | 9480  | 9790  | 10200 |
| 20            | 6130 | 6860 | 7480 | 7900 | 8210 | 8530 | 8830 | 9250 | 9660  | 9980  | 10400 |
| 12            | 6250 | 6990 | 7630 | 8060 | 8370 | 8690 | 9010 | 9440 | 9860  | 10180 | 10610 |
| 5             | 6620 | 7400 | 8070 | 8510 | 8860 | 9190 | 9530 | 9980 | 10420 | 10760 | 11210 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.