


# AGRIMAX SPARGO

TIRE SIZE	VF 320/90 R 54
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	TRATOR
VERSÃO	STANDARD
TIRE TYPE	TL
LI/SS	168 D



## DIMENSÕES IS STANDARD

SW (MM)	323	RIM REC	W 11
OD (MM)	1948	RIM ALT	W 10; DW 10; W 10 L; DW 11
SLR (MM)	910	ECE	E11-106R-009070
RC (MM)	5946	SRI	925

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.0	1.2	1.4	1.6	1.8	2.0	2.2	2.4	2.6	2.8	3.0	3.2	3.4	3.6	3.8	4.0	4.2	4.4
70	2230	2490	2800	3060	3215	3370	3475	3575	3760	3940	4095	4250	4380	4510	4640	4770	4975	5180
FROM 65 TO 40	2410	2690	3025	3305	3475	3640	3755	3865	4060	4260	4425	4595	4735	4875	5015	5155	5380	5600
30	2460	2745	3090	3375	3545	3715	3830	3945	4145	4345	4515	4690	4830	4975	5115	5260	5490	5715
20	2505	2800	3150	3440	3615	3790	3905	4020	4225	4430	4605	4780	4925	5070	5215	5360	5595	5825
10	2650	2960	3330	3635	3820	4005	4130	4255	4470	4685	4870	5055	5210	5360	5515	5670	5915	6160

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.