

# XL GRIP (L3)

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | 20.5 - 25  |
| <b>UM</b>           | US STANDARD                                      |
| <b>CONSTRUCTION</b> | ⊠ BIAS   |
| <b>MACHINERY</b>    | CARREGADORA / CARREGADORA /<br>TRATOR DE ESTEIRA |
| <b>VERSÃO</b>       | STANDARD   |
| <b>TIRE TYPE</b>    | TL   |



## DIMENSÕES US STANDARD

|                   |          |                 |           |
|-------------------|----------|-----------------|-----------|
| <b>CÓDIGO USA</b> | 94015832 | <b>RIM REC</b>  | 17.00/2.0 |
| <b>OD (IN)</b>    | 58.5     | <b>PR</b>       | 16        |
| <b>SLR (IN)</b>   | 26.9     | <b>TRA CODE</b> | E3/L3     |
| <b>RC (IN)</b>    | 173.0    |                 |           |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 40    | 51    |
|-----------|-------|-------|
| 30        | 12000 | -     |
| 5         | -     | 18200 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.