

# AS 504

**11.5/80 - 15.3****UM** US STANDARD**CONSTRUCTION**  BIAS**MACHINERY** TELESKOPIK YÜKLEYİCİ / TARLA  
RÖMORKU / UYGULAMALI MAKİNE /  
TELESKOPIK YÜKLEYİCİ**VERSION** STANDARD**TIRE TYPE** TL

119 A8

131 A8



## UNDEFINED US STANDARD

|                 |          |                |       |
|-----------------|----------|----------------|-------|
| <b>USA CODE</b> | 94018703 | <b>RC (IN)</b> | 100.0 |
| <b>SW (IN)</b>  | 11.4     | <b>RIM REC</b> | 9.00  |
| <b>OD (IN)</b>  | 34.1     | <b>PR</b>      | 10    |
| <b>SLR (IN)</b> | 15.0     |                |       |

## LOAD CAPACITY (LBS/TIRE)

| <b>MPH / PSI</b> | <b>49</b> |
|------------------|-----------|
| 5 FR             | 6020      |
| 15 FR            | 5110      |
| 20 FR            | 4820      |
| 25 FR            | 4300      |
| 5 DW             | 4200      |
| 15 DW            | 3570      |
| 20 DW            | 3360      |
| 25 DW            | 3000      |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.