

# AGRIMAX RT 855

<b>TIRE SIZE</b>	<b>380/85 R 28</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	PULVERIZADOR AGRÍCOLA / VINDIMADORA / TRATOR / CEIFEIRA / IMPLEMENTOS AGRÍCOLAS
<b>VERSÃO</b>	SPECIAL
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	133 A8/B



## DIMENSÕES IS STANDARD

<b>SW (MM)</b>	380	<b>RIM REC</b>	W 12
<b>OD (MM)</b>	1357	<b>RIM ALT</b>	W 11 ; W 13
<b>SLR (MM)</b>	606	<b>ECE</b>	E4-106R-000597
<b>RC (MM)</b>	4015	<b>SRI</b>	650

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6
50	1135	1320	1505	1690	1875	2060
40	1135	1320	1505	1690	1875	2060
30	1215	1415	1610	1810	2010	2205
10 LT	1525	1770	2020	2270	2520	2765
10 HT	1215	1415	1610	1810	2010	2205

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.