

# AT 621

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>385/65 - 19.5</b>                                   |
| <b>UM</b>           | IS STANDARD  |
| <b>CONSTRUCTION</b> | ⊠ BIAS   |
| <b>MACHINERY</b>    | KOMPAKTLADER / BAGGERLADER /<br>BAGGERLADER / RADLADER |
| <b>VERSION</b>      | STANDARD   |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 165 A2   |



## ABMESSUNGEN IS STANDARD

|                 |      |                |                 |
|-----------------|------|----------------|-----------------|
| <b>SW (MM)</b>  | 390  | <b>RIM REC</b> | 11.75           |
| <b>OD (MM)</b>  | 1020 | <b>RIM ALT</b> | 12.25           |
| <b>SLR (MM)</b> | 478  | <b>ECE</b>     | E11-106R-006419 |
| <b>RC (MM)</b>  | 3136 | <b>PR</b>      | 16              |

## LOAD CAPACITY (KG/TIRE)

|                   |             |
|-------------------|-------------|
| <b>KM/H / BAR</b> | <b>6.90</b> |
| 10                | 5150        |
| 0 (STATIONARY)    | 6700        |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.