DATA SHEET

PRINTED ON
21-04-2026

XL GRIP (L3)

TIRE SIZE	**26.5 - 25**
UM	US STANDARD
CONSTRUCTION	BIAS
MACHINERY	PALA CARICATRICE / PALA CARICATRICE / DOZER
VERSIONE	STANDARD
TIRE TYPE	TL

DIMENSIONI US STANDARD

CODICE USA	94027989	**RIM REC**	22.00/3.0
OD (IN)	68.5	**PR**	32
SLR (IN)	31.3	**TRA CODE**	L3
RC (IN)	202.8		

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	80
5	37500

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..