

## RT 857

|                  |                    |
|------------------|--------------------|
| <b>TIRE SIZE</b> | <b>320/85 R 24</b> |
| <b>UM</b>        | US STANDARD        |
| <b>MACHINERY</b> | TRACTOR            |
| <b>VERSION</b>   | STANDARD           |
| <b>TL/TT</b>     | TL                 |
| <b>LI/SS</b>     | 122 A8/B           |

### DIMENSIONS US STANDARD

|                 |          |                |                 |
|-----------------|----------|----------------|-----------------|
| <b>USA CODE</b> | 94052318 | <b>RC (IN)</b> | 135.8           |
| <b>SW (IN)</b>  | 13.0     | <b>RIM REC</b> | W 11            |
| <b>OD (IN)</b>  | 45.4     | <b>RIM ALT</b> | W 10 ; W 9      |
| <b>SLR (IN)</b> | 20.8     | <b>ECE</b>     | E11-106R-002976 |

### LOAD CAPACITY (LBS/TIRE)

| MPH / PSI   | 9    | 12   | 15   | 17   | 20   | 23   |
|-------------|------|------|------|------|------|------|
| <b>30</b>   | 1820 | 2120 | 2410 | 2710 | 3010 | 3310 |
| <b>25</b>   | 1820 | 2120 | 2410 | 2710 | 3010 | 3310 |
| <b>20</b>   | 1950 | 2270 | 2590 | 2910 | 3230 | 3540 |
| <b>5 LT</b> | 2450 | 2840 | 3240 | 3640 | 4030 | 4430 |
| <b>5 HT</b> | 1950 | 2270 | 2590 | 2910 | 3230 | 3540 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

