


# AGRIMAX RT 657

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>600/65 R 30</b>   |
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | MAȘINĂ DE RECOLTAT PODGORII /<br>TRACTOR / MAȘINĂ DE RECOLTARE                           |
| <b>VERSION</b>      | STANDARD   |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 155 D ; 158 A8   |



## DIMENSIUNI US STANDARD

|                 |          |                |                |
|-----------------|----------|----------------|----------------|
| <b>USA CODE</b> | 94032310 | <b>RC (IN)</b> | 181.5          |
| <b>SW (IN)</b>  | 24.1     | <b>RIM REC</b> | DW 20 B        |
| <b>OD (IN)</b>  | 60.7     | <b>RIM ALT</b> | W 18 L         |
| <b>SLR (IN)</b> | 27.4     | <b>ECE</b>     | E4-106R-001825 |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 9    | 12   | 15   | 17   | 20   | 23   | 29    | 35    |
|-----------|------|------|------|------|------|------|-------|-------|
| 40        | 4100 | 4780 | 5390 | 5990 | 6580 | 7100 | 7860  | 8540  |
| 30        | 4310 | 5030 | 5650 | 6280 | 6910 | 7450 | 8260  | 8970  |
| 25        | 4500 | 5250 | 5910 | 6560 | 7220 | 7780 | 8620  | 9370  |
| 20        | 4730 | 5510 | 6190 | 6890 | 7570 | 8170 | 9050  | 9830  |
| 5 LT      | 5500 | 6420 | 7220 | 8020 | 8830 | 9510 | 10540 | 11450 |
| 5 HT      | 4730 | 5510 | 6190 | 6890 | 7570 | 8170 | 9050  | 9830  |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.