


# AGRIMAX RT 765

<b>TYRE SIZE</b>	<b>360/70 R 28</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	TRACTOR / IMPLEMENTS
<b>VERSION</b>	STANDARD
<b>TYRE TYPE</b>	TL
<b>LI/SS</b>	125 D



## DIMENSIONS US STANDARD

<b>USA CODE</b>	94063048	<b>RC (IN)</b>	148.3
<b>SW (IN)</b>	14.1	<b>RIM REC</b>	W 11
<b>OD (IN)</b>	49.3	<b>RIM ALT</b>	W 10; W 12
<b>SLR (IN)</b>	22.8	<b>ECE</b>	E11-106R-005828

## LOAD CAPACITY (LBS/TYRE)

MPH / PSI	9	12	15	17	20	23
40	2010	2340	2660	2990	3320	3640
30	2110	2460	2800	3140	3480	3820
25	2200	2560	2920	3270	3640	3990
20	2300	2690	3060	3440	3810	4190
5 LT	2690	3130	3570	4010	4450	4880
5 HT	2300	2690	3060	3440	3810	4190

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.